



**SAFETY DATA SHEET**  
PROMATIC - MATT BLACK

Page 1  
Issued: 08/03/2010  
Revision No: 1

## 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

**Product name:** PROMATIC - GLOSS BLACK  
**Product code:** GW500  
**Company name:** PROMATIC  
Surrey House  
Hereford  
HR2 6JF  
England  
Tel: 01432 373350  
Fax: 01432 373360  
Email: [sales@htsspare.com](mailto:sales@htsspare.com)

## 2. HAZARDS IDENTIFICATION

**Classification under CHIP:** Extremely flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

**Workplace exposure limit:** This product does not have a workplace exposure limit.

**PBT:** This substance is not identified as a PBT substance.

**Directive 1999/45/EC:** This mixture meets the criteria for classification as dangerous in accordance with Directive 1999/45/EC.

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

- Hazardous ingredients:** 1-METHOXY-2-PROPANOL (\*WEL) 1-10%  
EINECS: 203-539-1 CAS: 107-98-2  
[-] R10
- 2-BUTOXYETHANOL 1-10%  
EINECS: 203-905-0 CAS: 111-76-2  
[Xn] R20/21/22; [Xi] R36/38
  - ACETONE 30-50%  
EINECS: 200-662-2 CAS: 67-64-1  
[F] R11; [Xi] R36; [-] R66; [-] R67
  - BUTANE (\*WEL) 10-30%  
EINECS: 203-448-7 CAS: 106-97-8  
[F+] R12
  - ISOBUTANE (\*WEL) 1-10%  
EINECS: 200-857-2 CAS: 75-28-5  
[F+] R12

**SAFETY DATA SHEET**

PROMATIC – MATT BLACK

- PROPANE (\*WEL) 10-30%  
EINECS: 200-827-9 CAS: 74-98-6  
[F+] R12
- XYLENE 1-10%  
EINECS: 215-535-7 CAS: 1330-20-7  
[-] R10; [Xn] R20/21; [Xi] R38

**4. FIRST AID MEASURES**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

**Exposure hazards:** Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour may travel considerable distance to source of ignition and flash back.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

**7. HANDLING AND STORAGE**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Hazardous ingredients:** 1-METHOXY-2-PROPANOLUK - 8 hour TWA: 375 mg/m<sup>3</sup>UK - 15 min. STEL: 560 mg/m<sup>3</sup>

## • 2-BUTOXYETHANOL

UK - 8 hour TWA: 25 ppm

UK - 15 min. STEL: 50 ppm

## • ACETONE

UK - 8 hour TWA: 1210 mg/m<sup>3</sup>UK - 15 min. STEL: 3620 mg/m<sup>3</sup>

## • BUTANE

UK - 8 hour TWA: 1450 mg/m<sup>3</sup>UK - 15 min. STEL: 1810 mg/m<sup>3</sup>

## • ISOBUTANE

UK - 8 hour TWA: 2400 mg/m<sup>3</sup>UK - 15 min. STEL: 9600 mg/m<sup>3</sup>

## • PROPANE

UK - 8 hour TWA: 1800 mg/m<sup>3</sup>UK - 15 min. STEL: 7200 mg/m<sup>3</sup>

## • XYLENE

UK - 8 hour TWA: 220 mg/m<sup>3</sup>UK - 15 min. STEL: 441 mg/m<sup>3</sup>**Engineering measures:** Ensure there is sufficient ventilation of the area.**Respiratory protection:** Respiratory protection not required.**Hand protection:** Protective gloves.**Eye protection:** Safety glasses. Ensure eye bath is to hand.**Skin protection:** Protective clothing.**9. PHYSICAL AND CHEMICAL PROPERTIES****State:** Aerosol**Colour:** White**Odour:** Characteristic odour**Solubility in water:** Insoluble**Flammability limits %: lower:** 0.8**upper:** 9.0**Flash point°C:** <0**VOC g/l:** 618

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions. Stable at room temperature.

**Conditions to avoid:** Heat. Hot surfaces. Sources of ignition. Flames.

**Materials to avoid:** Strong oxidising agents. Strong acids.

**Haz. decomp. products:** In combustion emits toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

**Acute effects:** Irritating to eyes.

**11. TOXICOLOGICAL INFORMATION (SYMPTOMS)**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Readily absorbed into soil.

**Persistence and degradability:** Biodegradable.

**Bioaccumulative potential:** No bioaccumulation potential.

**Other adverse effects:** Negligible ecotoxicity.

**PBT identification:** This substance is not identified as a PBT substance.

**13. DISPOSAL CONSIDERATIONS**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION**

**ADR / RID**

**UN no:** 1950

**ADR Class:** 2

**Classification code:** 5F

**Shipping name:** AEROSOLS

**Labelling:** 2.1



**SAFETY DATA SHEET**

PROMATIC – MATT BLACK

**IMDG / IMO**

**UN no:** 1950 **Class:** 2  
**EmS:** F-D,S-U **Marine pollutant:** .  
**Labelling:** 2.1

**IATA / ICAO**

**UN no:** 1950 **Class:** 2  
**Labelling:** 2.1

**15. REGULATORY INFORMATION (CHIP)**

**Hazard symbols:** Extremely flammable.  
 Irritant.



**Risk phrases:** R12: Extremely flammable.  
 R36: Irritating to eyes.  
 R66: Repeated exposure may cause skin dryness or cracking.  
 R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S38: In case of insufficient ventilation, wear suitable respiratory equipment.

**Precautionary phrases:** Contains methyl methacrylate. May produce an allergic reaction.  
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.  
 Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

**Haz. ingredients (label):** ACETONE

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

**16. OTHER INFORMATION**

**Other information:** This safety data sheet is prepared in accordance with Regulation (EC) No 1907/2006.

\* indicates text in the SDS which has changed since the last revision.

**Risk phrases used in s.3:** R10: Flammable.  
 R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.  
 R36/38: Irritating to eyes and skin.  
 R11: Highly flammable.  
 R36: Irritating to eyes.

**SAFETY DATA SHEET**  
PROMATIC – MATT BLACK

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

R12: Extremely flammable.

R20/21: Harmful by inhalation and in contact with skin.

R38: Irritating to skin.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.