

SAFETY DATA SHEET **Multitrans MPC**

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Multitrans MPC

Product number 7285

Internal identification GHS21529

REACH registration notes Not applicable.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Transmission oil.

Uses advised against Non specified unless otherwise stated within this MSDS

1.3. Details of the supplier of the safety data sheet

Supplier Morris Lubricants

> Castle Foregate Shrewsbury SY1 2EL

08.45 - 17.00 GMT T: (+44)(0)1743 232200 F: (+44)(0)1743 353584 sds@morris-lubricants.co.uk

1.4. Emergency telephone number

Emergency telephone +44(0)1743 232200 (08.45 - 17.00 GMT)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Not Classified

Health hazards Elicitation - EUH208

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or R52/53.

1999/45/EC)

2.2. Label elements

Hazard statements H412 Harmful to aquatic life with long lasting effects.

> EUH208 Contains Acetamide,2-hydroxy-,N,N-dicocoalkyl derivs., 1-(tert-Dodecylthio) propan-2-ol, 1,2-Propanediol,3-amino-,N,N-dicoco alkyl derivs.. May produce an allergic reaction.

P273 Avoid release to the environment. **Precautionary statements**

P501a Dispose of contents/container to hazardous or special waste collection point.

Multitrans MPC

2.3. Other hazards

None identified. This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Lubricating Oil (petroleum), C20-C50, hydrotreated neutral oil

30-60%

 REACH registration number: 01-

2119474889-13-XXXX

Classification

Classification (67/548/EEC or 1999/45/EC)

Asp. Tox. 1 - H304

Highly refined mineral oil (C15 - C50)

1-5%

CAS number: — EC number: 276-738-4

REACH registration number: 01-

2119474889-13-XXXX

Classification

Classification (67/548/EEC or 1999/45/EC)

Asp. Tox. 1 - H304 -

Distillates (petroleum), hydrotreated light paraffinic

1-5%

CAS number: 64742-55-8

EC number: 265-158-7

REACH registration number: 01-

2119487077-29-XXXX

Classification

Classification (67/548/EEC or 1999/45/EC)

Asp. Tox. 1 - H304

Thiophene, tetrahydro- 1,1-dioxide, 3-(C9-11-isoalkyoxy)

1-5%

derivs, C10-rich

CAS number: —

EC number: 800-172-4

REACH registration number: 01-

2119969520-35-XXXX

Classification

Aquatic Chronic 2 - H411

Classification (67/548/EEC or 1999/45/EC)

N;R51/53.

Xn;R65.

Acetamide,2-hydroxy-,N,N-dicocoalkyl derivs.

<1%

CAS number: —

EC number: 471-920-1

REACH registration number: 01-

0000019770-68-XXXX

Classification

Classification (67/548/EEC or 1999/45/EC)

Skin Sens. 1 - H317

Xi;R38. R43.

Multitrans MPC

1-(tert-Dodecylthio) propan-2-ol <1%

CAS number: — EC number: 266-582-5 REACH registration number: 01-

2119953277-30-XXXX

M factor (Acute) = 1 M factor (Chronic) = 1

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Sens. 1 - H317 N;R50/53. R43.

Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

1,2-Propanediol,3-amino-,N,N-dicoco alkyl derivs.

CAS number: — EC number: 482-000-4 REACH registration number: 01-

0000020142-86-XXXX

<1%

Classification Classification (67/548/EEC or 1999/45/EC)

Skin Sens. 1 - H317 Xi;R38. R43,R52/53.

Aquatic Chronic 3 - H412

Diphenylamine <1%

Classification Classification (67/548/EEC or 1999/45/EC)

Acute Tox. 3 - H301 T;R23/24/25. N;R50/53. R33.

Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT RE 2 - H373 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues.

Inhalation If spray/mist has been inhaled, proceed as follows. Move affected person to fresh air and

keep warm and at rest in a position comfortable for breathing. Get medical attention if any

discomfort continues.

Ingestion Get medical attention if any discomfort continues. Do not induce vomiting.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms

occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

Multitrans MPC

General information Do not induce vomiting. Aspiration hazard if swallowed. Entry into the lungs following

ingestion or vomiting may cause chemical pneumonitis.

Inhalation Upper respiratory irritation.

Ingestion Aspiration hazard if swallowed. Entry into the lungs following ingestion or vomiting may cause

chemical pneumonitis.

Skin contact Prolonged skin contact may cause redness and irritation.

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion

products

Fire or high temperatures create: Carbon monoxide (CO). Carbon dioxide (CO2). Nitrous gases (NOx). Sulphurous gases (SOx). Other unidentified organic and inorganic gases and

compounds, some of which may be toxic.

5.3. Advice for firefighters

Protective actions during

firefighting

Control run-off water by containing and keeping it out of sewers and watercourses.

for firefighters

Special protective equipment Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8. In case of spills, beware of slippery floors and

surfaces.

6.2. Environmental precautions

Contain spillage with sand or earth. Avoid the spillage or runoff entering drains, sewers or **Environmental precautions**

watercourses. The product is insoluble in water and will spread on the water surface.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain spillage with sand or earth. Collect spillage for reclamation or disposal in sealed

> containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Multitrans MPC

Usage precautions Always remove oil with soap and water or skin cleaning agent, never use organic solvents. Do

not use oil-contaminated clothing or shoes, and do not put rags moistened with oil into

pockets. Avoid contact with eyes and prolonged skin contact. Avoid spilling.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

Storage class Miscellaneous hazardous material storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

Lubricating Oil (petroleum), C20-C50, hydrotreated neutral oil

Long-term exposure limit (8-hour TWA): ACGIH 5 mg/m³

Short-term exposure limit (15-minute): 10 mg/m³

Highly refined mineral oil (C15 - C50)

Long-term exposure limit (8-hour TWA): ACGIH 5 ppm Short-term exposure limit (15-minute): ACGIH 10 ppm

Diphenylamine

Short-term exposure limit (15-minute): WEL 20 mg/m³ Long-term exposure limit (8-hour TWA): WEL 10 mg/m³

ACGIH = American Conference of Governmental Industrial Hygienists.

WEL = Workplace Exposure Limit

Bis(nonylphenyl)amine

DNEL Industry - Dermal; Long term systemic effects: 0.62 mg/kg

Industry - Inhalation; Long term systemic effects: 4.37 mg/m³ Consumer - Dermal; Long term systemic effects: 0.31 mg/kg Consumer - Inhalation; Long term systemic effects: 1.09 mg/m³ Consumer - Oral; Long term systemic effects: 0.31 mg/kg

PNEC - Marine water; 0.01 mg/l

Sediment (Freshwater); 132000 mg/kgSediment (Marinewater); 13200 mg/kg

Soil; 263000 mg/kgFresh water; 0.1 mg/l

Diphenylamine (CAS: 122-39-4)

DNEL Workers - Dermal; Long term systemic effects: 0.62 mg/kg

Workers - Inhalation; Long term systemic effects: 4.37 mg/m³ Consumer - Dermal; Long term systemic effects: 0.31 mg/kg Consumer - Inhalation; Long term systemic effects: 1.09 mg/m³ Consumer - Oral; Long term systemic effects: 0.31 mg/kg

Multitrans MPC

PNEC - Fresh water; 0.051 mg/l

Marine water; 0.0051 mg/l
Intermittent release; 0.51 mg/l
Sediment (Freshwater); 9320 mg/kg
Sediment (Marinewater); 932 mg/kg

Soil; 1860 mg/kgSTP; 1 mg/l

8.2. Exposure controls

Protective equipment





Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure

limits for the product or ingredients.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. The following protection should be worn: Chemical splash goggles or

face shield.

Hand protection The most suitable glove should be chosen in consultation with the glove

supplier/manufacturer, who can provide information about the breakthrough time of the glove

material.

Other skin and body

protection

Use barrier creams to prevent skin contact.

promptly with soap and water if skin becomes contaminated.

Respiratory protection
No specific recommendations. Respiratory protection must be used if the airborne

contamination exceeds the recommended occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Red.

Odour Characteristic. Oil-like.

Odour threshold Not determined.

pH Not applicable.

Melting point -51°C Pour point

Initial boiling point and range >320°C @ 101.3 kPa

Flash point 173°C PMCC (Pensky-Martens closed cup).

Other flammability Product is not flammable but on excessive heating may become combustible.

Vapour pressure <0.1 kPa @ 20°C

Vapour density Not determined.

Relative density 0.850 @ 15.6°C

Solubility(ies) Insoluble in water. Soluble in the following materials: Organic solvents.

Multitrans MPC

Partition coefficient Not determined. log Kow: > 7 This figure is typical of mineral oil.

Auto-ignition temperature >320°C

Decomposition Temperature Not determined.

Viscosity 33 cSt @ 40°C

Explosive properties Not considered to be explosive.

Explosive under the influence

of a flame

Not considered to be explosive.

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria

for classification as oxidising.

9.2. Other information

Volatile organic compound The product is a complex mixture, the majority of which would not be classed as a VOC.

However it cannot be discounted that trace or low levels of VOC's may be present.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Does not decompose when used and stored as recommended.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

Oxides of carbon. Protection against nuisance dust must be used when the airborne

products concentration exceeds 10 mg/m3.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

General information This product has low toxicity. Only large quantities are likely to have adverse effects on

human health. May produce an allergic reaction.

Inhalation Unlikely to be hazardous by inhalation because of the low vapour pressure of the product at

ambient temperature.

Ingestion No harmful effects expected from quantities likely to be ingested by accident.

Skin contact Skin irritation should not occur when used as recommended. Repeated exposure may cause

skin dryness or cracking.

Eye contact May cause temporary eye irritation.

Multitrans MPC

Acute and chronic health

Prolonged or repeated contact with used oil may cause serious skin diseases, such as

hazards

dermatitis and skin cancer.

SECTION 12: Ecological Information

EcotoxicityThe product contains a substance which is harmful to aquatic organisms and which may

cause long-term adverse effects in the aquatic environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability The product is not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potentialBioaccumulation is unlikely to be significant because of the low water-solubility of this product.

Partition coefficient Not determined. log Kow: > 7 This figure is typical of mineral oil.

12.4. Mobility in soil

Mobility The product is non-volatile. The product is insoluble in water and will spread on the water

surface.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste, residues, empty containers, discarded work clothes and contaminated cleaning

materials should be collected in designated containers, labelled with their contents. This

material and its container must be disposed of as hazardous waste.

Disposal methods Dispose of waste via a licensed waste disposal contractor.

Waste class European waste catalogue (EWC) number = 13 02 05* (mineral based non-chlorinated

engine, gear & lubricating oils)

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

Multitrans MPC

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Health and Safety at Work etc. Act 1974 (as amended).

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

Special Waste regulations 1996.

Control of Pollution (Oil Storage) (England) Regulations 2001

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

EU legislation Dangerous Preparations Directive 1999/45/EC.

Dangerous Substances Directive 67/548/EEC.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Guidance Workplace Exposure Limits EH40.

Safety Data Sheets for Substances and Preparations.

Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision date 08/02/2016

Revision 1

SDS number 21529

Risk phrases in full R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Multitrans MPC

Hazard statements in full H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH208 Contains Acetamide,2-hydroxy-,N,N-dicocoalkyl derivs., 1-(tert-Dodecylthio) propan-2-ol, 1,2-Propanediol,3-amino-,N,N-dicoco alkyl derivs.. May produce an allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.