

FIXT BRAKE, PIPE & AIR SEALANT

Page: 1

Compilation date: 14/11/2011

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: FIXT BRAKE, PIPE & AIR SEALANT

Product code: FX085568

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Quest Consumables Limited

Contact details: Seymour Road

Nuneaton Warwickshire CV11 4LB

TELEPHONE +44 (0)24 76 322126

FACSIMILE +44 (0)24 76 322117

E MAIL info@fixtconsumables.com

EMERGENCY TELEPHONE NUMBER +44 (0)24 76 322196

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: Xi: R36/38

Most important adverse effects: Irritating to eyes and skin.

2.2. Label elements

Label elements under CHIP:

Hazard symbols: Irritant.



Risk phrases: R36/38: Irritating to eyes and skin.

Safety phrases: S24/25: Avoid contact with skin and eyes.

S37/39: Wear suitable gloves and eye / face protection.

2.3. Other hazards

PBT: This substance is not identified as a PBT substance.

Section 3: Composition/information on ingredients

FIXT BRAKE, PIPE & AIR SEALANT

Page: 2

3.2. Mixtures

Hazardous ingredients:

METHACRYLIC DIESTER OF POLYETHYLENE GLYCOL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	25852-47-5	-	-	10-30%
OCTANOL				
203-917-6	11187-5	Xi: R36/38	-	1-10%
AMORPHOUS	SILICA			
231-545-4	7631-86-9	Substance with a Community	-	1-10%
		workplace exposure limit.		
ETHYLENE GL	YCOL			
203-473-3	107-21-1	Xn: R22	-	1-10%
CUMENE HYD	ROPEROXIDE			
201-524-7	80-15-9	O: R7; Xn: R21/22; T: R23; C: R34;	-	<1%
		Xn: R48/20/22; N: R51/53		

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

FIXT BRAKE, PIPE & AIR SEALANT

Page: 3

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

AMORPHOUS SILICA

Workplace exposure limits:

Respirable dust

State	8 hour TWA:	15 min. STEL:	8 hour TWA:	15 min. STEL:
EU	-	-	3 ma/m3	-

FIXT BRAKE, PIPE & AIR SEALANT

Page: 4

ETHYLENE GLYCOL

UK	52 mg/m3 (vapour)	104 mg/m3 (vapour)	-	-
----	-------------------	--------------------	---	---

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

9.2. Other information

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

FIXT BRAKE, PIPE & AIR SEALANT

Page: 5

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may

cause coughing or wheezing.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: Not applicable.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This substance is not identified as a PBT substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: Not classified.

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Section 15: Regulatory information

FIXT BRAKE, PIPE & AIR SEALANT

Page: 6

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: R7: May cause fire.

R21/22: Harmful in contact with skin and if swallowed.

R22: Harmful if swallowed.

R23: Toxic by inhalation.

R34: Causes burns.

R36/38: Irritating to eyes and skin.

R48/20/22: Harmful: danger of serious damage to health by prolonged exposure

through inhalation and if swallowed.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.